

# ZHEJIANG DEJIA NEW MATERIAL CO.,LTD



## TECHNICAL DATA SHEET

**Product:** -PVC half panama double side coated Fabric (5205)

**Application:**

Ventilation

|                                    |                                   |
|------------------------------------|-----------------------------------|
| Support Cloth ( DIN 6000 )         | Polyester                         |
| Specification ( DIN EN 1049-2 )    | 20*10 per inch(half panama weave) |
| Yarn (dtex) ( DIN EN ISO 2060 )    | 1000*2000 D                       |
| Type of Coating                    | pvc coated on both sides          |
| Total Weight ( DIN EN ISO 2286-2 ) | 700g/m <sup>2</sup>               |
| Width ( DIN EN ISO 2286-1)         | UP TO 3.2M                        |
| Tensile strength ( DIN 53354 )     | 2600/2600 N/5CM                   |
| Tear strength ( DIN 53356 )        | 300/300N/5CM                      |
| Adhesion Strength                  | 100N/5CM                          |
| Low Temperature-No Crack At        | -30°C to +70°C                    |
| Flame Retardant                    | NFPA701,M2,B1                     |

**Packing:** craft paper or PE foam

**Features:**

- A: UV resistant , FR (NFPA701,B1,M2)
- B: Cold resistant, Anti-Mildow
- C: Glossy and Matt surface
- D: Lacquered are available as requests
- E: Color, weight can be customized
- F: Antistatic available.