

# ZHEJIANG DEJIA NEW MATERIAL CO.,LTD



## TECHNICAL DATA SHEET

**Product:** -PVC plain weave double side coated Fabric (7701)

Blockout, with both lacquered. UV Treated, Anti Fungus.

**Application:**

Tents, Pergola roofing

Support Cloth ( DIN 6000 )	Polyester
Specification ( DIN EN 1049-2 )	23*23 per inch(plain weave)
Yarn (dtex) ( DIN EN ISO 2060 )	1000*1000 D
Type of Coating	pvc coated on both sides
Total Weight ( DIN EN ISO 2286-2 )	650g/m2
Width ( DIN EN ISO 2286-1)	UP TO 3.2M
Tensile strength ( DIN 53354 )	3300/3200 N/5CM
Tear strength ( DIN 53356 )	350/320N/5CM
Adhesion Strength	100N/5CM
Low Temperature-No Crack At	-30°C to +70°C
Flame Retardant	NFPA701,M2,B1

**Packing:** craft paper or PE foam

**Features:**

- A: UV resistant , FR (NFPA701,B1,M2)
- B: Cold resistant, Anti-Mildow
- C: Glossy and Matt surface
- D: Lacquered are available as requests
- E: Color, weight can be customized