

ZHEJIANG DEJIA NEW MATERIAL CO.,LTD



TECHNICAL DATA SHEET

Product: -PVC plain weave double side coated Fabric DCW 1050 (3109)

Application:

Boat fabric

| | |
|------------------------------------|-----------------------------|
| Support Cloth (DIN 6000) | Polyester |
| Specification (DIN EN 1049-2) | 28*26 per inch(plain weave) |
| Yarn (dtex) (DIN EN ISO 2060) | 1000*1000 D |
| Type of Coating | pvc coated on both sides |
| Total Weight (DIN EN ISO 2286-2) | 1050g/m ² |
| Width (DIN EN ISO 2286-1) | UP TO 3.2M |
| Tensile strength (DIN 53354) | 4000/4000 N/5CM |
| Tear strength (DIN 53356) | 400/400N/5CM |
| Adhesion Strength | 120/5cm |
| Low Temperature-No Crack At | -30°C to +70°C |
| Flame Retardant | NFPA701,M2,B1 |

Packing: craft paper or PE foam

Features:

- A: UV resistant , FR (NFPA701,B1,M2
- B: Cold resistant, Anti-Mildow
- C: Glossy and Matt surface
- D: Lacquered are available as requests
- E: Color, weight can be customized